
Scuba II Electronic Pooltester



Test equipment for the responsible private swimming pool and whirlpool operator

Scuba II

Every pool owner should check the most important parameters in his pool at regular intervals. This is the only way to ensure that water quality is maintained at an right level and to arrange dosing in an optimum manner.

The Scuba II enables the operator to check the pool water quickly and accurately. The integrated sample chamber filled by immersing it in the water. A tablet reagent is added and generates a characteristic colour which can be measured using the photometric principle. The result is then displayed on the screen.

Five parameters, free chlorine, total chlorine, pH, alkalinity and stabilizer (cyanuric acid) are measured within a few minutes. Water analysis becomes a pleasure rather than a chore and more time is left for enjoying the pleasure of the pool.

If the Scuba II falls into the water it will simply float and, of course, it is watertight.

Why not try this compact test equipment – after all, the knowledge that you are safe in a thoroughly hygienic pool is worth a little effort.

Technical Data

temperature-compensated LED (λ = 530 nm) and photo-sensor
2 batteries (AAA), capacity minimum 500 tests
automatic switch-off approx. 5 minutes after last key press
LCD
145 x 70 x 45 mm

approx. 165 g (incl. batteries)

relative humidity: 30 - 90%,

temperature: 5 – 40°C

non-condensing

CE-Conformity

Weight

Operating

conditions

Highlights

- Modern, ergonomic design
- · User friendly Handling
- Watertight housing*
- Large display
- * as defined in IP 68, 1 hour at 0.1 meter



Refill pack

Article Code Refill pack for Scuba II 52 56 00

20 DPD No.1 Photometer tablets 10 DPD No.3 Photometer tablets 10 PHENOL RED Photometer tablets 10 CyA-Test tablets

10 Alka-M-Photometer tabletsn

Packaging unit = 12 packs



http://scuba-ll.lovibond.com

Delivery content

- Scuba II in a robust plastic box
- Tablet reagents each 20 DPD No.1 & Phenol Red Photometer each 10 DPD No.3, CyA-Test & Alka-M-Photometer
- 2 batteries (AAA)
- Stirring rod
- Instruction manual

Order code: 21 61 00

Determination	Range	Resolution	Accuracy
Chlorine, free	0.1 - 6 mg/l Cl ₂	0.1 mg/l	0 - 1 mg/l ± 0.1 mg/l ; 1 - 2 mg/l ± 0.2 mg/l 2 - 3 mg/l ± 0.4 mg/l ; 3 - 6 mg/l ± 0.5 mg/l
Chlorine, total	0.1 - 6 mg/l Cl ₂	0.1 mg/l	$0 - 1 \text{ mg/l} \pm 0.1 \text{ mg/l}$; $1 - 2 \text{ mg/l} \pm 0.2 \text{ mg/l}$ $2 - 3 \text{ mg/l} \pm 0.4 \text{ mg/l}$; $3 - 6 \text{ mg/l} \pm 0.5 \text{ mg/l}$
pH Value	6.5 - 8.4 pH	0.1 pH	± 0.2 pH
Stabilizer (cyanuric acid)	1 - 160 mg/l	1.0 mg/l	$1 - 50 \text{ mg/l} \pm 10 \text{ mg/l}$; $50 - 160 \text{ mg/l} \pm 20 \text{ mg/l}$
Alkalinity (total)	0 - 300 mg/l CaCO₃	1.0 mg/l	± 50 mg/l